



UA9 Features



Built-in WiFi for a Mobile Workspace

Enables mobile workforce expansion with on-the-go access to virtual desktops through built-in WiFi and wired connectivity



Energy Efficiency, Reduced E-waste

UA9 cuts electricity costs with Intel® Alder Lake N100 CPU, using less power for prolonged device life and exceptional processing



Maximize Durability, Minimize Cost

The fanless UA9 eliminates the necessity for moving components, providing enhanced durability and dependability



Dual Monitor Support for Optimal Visuals

Elevate your visual experience with UA9's support for up to two UHD/4K displays, creating an immersive workspace effortlessly



15.6" LCD Screen for Greatness

UA9 employs a 15.6-inch LCD screen with a Numpad keyboard for increased productivity in intensive workplaces



Support IGEL OS / Win10 IoT Enterprise LTSC

Support multiple operating systems tailored to align with specific use cases and IT infrastructure requirements perfectly

UA9 TC156-AN

	formance	
$\boldsymbol{\mu}$	$T \cap r m \circ n \cap c c$	э.

CPU	Intel® Alder Lake N100 processor supports up to 3.4GHz max turbo frequency, Quad Core four threads	
Memory	8GB DDR4-3200MHz single channel	
Multiple Display	15.6" full HD LCD, 1 HDMI 1.4, USB-C Alt mode	
Display Resolution	Full HD on LCD, 4K 60Hz on connected displays (Max)	
Brightness (typical)	250 cd/m² typ.	
Viewing Angle	CR(>10):85/85 (V/H) typ.	
Graphic & Multimedia	 Intel® 12th UHD Graphics 24EUs Full HD 2MP webcam with microphone HEVC, VP9, and AVC decode support Support AVX2 instruction sets 	

Expandability

WiFi	 Onboard combo WiFió, 2 internal antenna (RTL8852BE) Bluetooth 5.2
Storage	 M.2 2280 M Key 128G SATA SSD Micro SD Card Reader (Windows support only)
LAN	RJ-45 10/100/1000Mbps
USB	3 USB-A 3.2 Gen1, 1 USB-C 3.2 Gen1 with DP Alt mode, power delivery
Audio	Combo audio jack for headset & Internal speakers
Power	USB Type-C 65W power adapter
Battery	Polymer 3S1P 11.4V/3950mAh/45W Li-Polymer Battery, 3 cells
Keyboard Language	German, Spanish, French, English, Dutch

Security / Manageability

Security Lock	Kensington lock slot
WoL	RJ45 LAN with standby power design supports Magic Packet wake-up event
TPM	Infineon TPM 2.0

Environment

Cooling	Passive cooling (Noise-Free)
Operating Temperature	0 °C to 35 °C, 32 °F to 95 °F
Operating Humidity	20% - 80% non-condensing

Dimension (w x h x d) & Weight: 244 x 21.6 x 368mm / 1.8kg

Warranty Policy:

5-year limited warranty, excluding components*

* For detailed warranty policy, refer to UltrArmor's official website FAQ page

Note: UltrArmor retains the authority to modify, correct, cancel, and/or enhance information, as well as products and programs described in such information, at any time without prior notice.